

ENKOfeed high-speed nail feeder

The ENKOTEC high-speed nail feeder type FRS01 or FLS01 has been designed for feeding nails into thread rollers, collators and other equipment for the production and processing of nails. The ENKOfeed is made of high quality material to ensure long and stable production.

The ENKOfeed comes in a clockwise and counter clockwise version delivered with discharge made for the ENKOTEC Thread Rolling Machine and the ENKOTEC Collator.

The capacity of the ENKOfeed is suitable for the fastest machines on the market.



ENKOfeed advantages:

- High production speed
- High-quality long lasting springs
- High-quality materials
- Easy adjustment with eccentrics
- CW and CCW versions
- Air jets to increase speed

ENKOfeed Specifications

	FRS01	FLS01
Rotation direction (Seen from the top)	CW	CCW
Capacity	900 npm - 3500 npm Depending on nail length, head type and nail shank profile	
Nail dimensions and type	Ø1,8 - Ø4,2 (.071"-.165") 28 mm - 105 mm (1.1"-4") Round head, offset head and D-head nails Profiled and smooth shank nails	
Discharge height	534 mm ±3mm (21" ±0.125")	
Discharge position	412 mm from center (16.2")	
Bowl diameter	825mm (32.500")	
Overall height	613 mm (24.2")	
Weight	380 kg (840 lbs)	
Discharge Handling	ENKOTEC style discharge profile Lifting eye at center of gravity	
Compressed air consumption	Adjustable, up to 13 m ³ /h at 5 bar	
Control	Variable frequency controller. Calibrated frequency.	
Power supply and consumption	220V, 6 A 50-60Hz or 110V, 12A 50-60 Hz	



Head Office & Production - ENKOTEC A/S · Sverigesvej 26 · DK-8660 Skanderborg
Tel.: +45 8652 4444 · Fax: +45 8652 4199 · sales@enkotec.dk · www.enkotec.com
Sales Office South & Central America · Tel.: +54 911 5102 2090 · max@enkotec.dk

Sales & Service USA/Canada/Mexico · ENKOTEC COMPANY, INC. · 31200 Solon Road, Solon · Ohio 44139, USA
Tel.: +1 440 349-2800 · Fax: +1 440 349-3575 · sales@enkotec.com · www.enkotec.com